



## Benessere Pro

- Open combustion chamber
- Dual heat exchangers
- Three way valve
- Water temperature stabilization system
- Automatic bypass
- Min and Max heating water pressure control
- Automatic gas flow control
- Heat monitoring and heat adjustment systems
- Ability to connect to room, outside, and floor-heating safety thermostats
- Customizable functions
- Digital display
- Instant and continuous hot water, reliable and independent heating
- Highest efficiency
- Latest electronic and mechanical systems
- Three speed circulator pump
- Italian sanitary water heat exchanger
- Atmospheric burner with auto-ignition
- Ionized flame protection
- controls troubleshooting system
- Anti-freeze and anti-lock systems
- Quick reactions and comfort systems

This model is appropriate for:

- Units up to 250 square meters

technical informations	Units	Benessere Pro
Heating Capacity – In	kW	31.3
Heating Capacity – Out	kW	29
Max. Water Temp. – Heating	°C	90
Max. Water Temp. – Sanitary	°C	63
Min. Start-up Water Pressure	bar	0.15
Max. Pump Height	m.w.c	5
Expansion Vessel Capacity	lit	8
Pipe Diameter – Heating	inch	3/4
Pipe Diameter – Sanitary	inch	1/2
Pipe Diameter – Gas Inlet	inch	3/4
Chimney Diameter	cm	15
Net. Weight	kg	32
Width	mm	450
Height	mm	740
Depth	mm	332